Amendments to the Claims:

This listing of claims replaces all claims as filed in the PCT application:

Listing of Claims:

- 1. (Currently amended) An inkjet recording element comprising a support having thereon at least one image-receiving layer, said inkjet recording element containing colloidal particles having a charged or chargeable surface and having associated therewith at least two <u>water-soluble</u> polymers having ionised or ionisable groups thereon, wherein one of those polymers has ionised or ionisable groups of opposite charge to that of the surface of the colloidal particles and another of those polymers has ionised or ionisable groups the same as that of the surface of the colloidal particles.
- 2. (Currently amended) An element according to as claimed in claim 1 wherein the colloidal particles are organic, inorganic or a composite thereof.
- 3. (Currently amended) An element according to either of the preceding claims as claimed in claim 1 wherein the colloidal particles are negatively charged and are selected from the class consisting of a silica, surface-treated silica, zinc oxide, zirconium oxide, aluminium oxide, titanium oxide, barium sulfate, kaolin clay, calcined clay, montmorillonite and talc.
- 4. (Currently amended) An element according to either of elaims 1 and 2 as claimed in claim 1 wherein the colloidal particles are positively charged and are selected from the class consisting of a silica, surface-treated silica, aluminium oxide, zinc oxide, magnesium oxide and calcium carbonate.
- 5. (Currently amended) An element according to any one of the preceding claims as claimed in claim 1 wherein the particles are colloidal silica, silica gel, hydrous silica or fumed silica.

- 6. (Currently amended) An element according to any one of the preceding claims as claimed in claim 1 wherein the equivalent spherical diameter of the colloidal particles is from about 0.01 to about 10μm.
- 7. (Currently amended) An element according to as claimed in claim 6 wherein the equivalent spherical diameter of the colloidal particles diameter is from about 0.04 to about 0.5 µm.
- 8. (Currently amended) An element according to any one of the preceding claims as claimed in claim 1 wherein a polymer includes a monomer that has a positive charge or can be induced to have a positive charge and is independently selected from the class consisting of allylamine, ethyleneimine, vinylamine, 2-vinylpyridine, 4-vinylpyridine, diallyldimethylammonium, 2-vinylpiperidine, 4-vinylpiperidine, 2-butylmethacryloxyethyltrimethyl ammonium, 4-vinybenzyltrimethylammonium, N,N'-bis 2,2,6,6-tetramethyl-4-piperidine, dimethyliminomethylene, butyl acrylate methacryloxyethyltrimethylammonium and a salt or derivative thereof.
- 9. (Currently amended) An element according to any one of the preceding-claims as claimed in claim 1 wherein a polymer is selected from polyethyleneimine, poly(4-vinylpyridine) and cationically-modified polyvinyl alcohol.
- elaims 1 to 7 as claimed in claim 1 wherein a polymer includes a monomer that has a negative charge or can be induced to have a negative charge and is independently selected from the class consisting of styrenesulfonic acid, vinylsulfonic acid, acrylic acid, 2-acrylamido-2-methyl-propane sulfonic acid, maleic anhydride, maleic acid, ethylene sulfonic acid, methacrylic acid, vinylsulfuric acid, ethylenephosphonic acid, maleic acid,

2-methacryloxyethane-1-sulfonic acid, 3-methacryloxyethane-1-sulfonic acid, vinylbenzoic acid, 3-(vinyloxy)propane-1-sulfonic acid, 4-vinylphenol, 4-vinyl-phenylsulfuric acid, 4-n-vinylsuccinamic acid and a salt or derivative thereof.

- 11. (Currently amended) An element according to any one of claims 1 to 7 and 10 as claimed in claim 1 wherein a polymer is selected from the class consisting of a sodium polystyrene sulfonate, a polystyrene sulfonate salt, a copolymer of styrene sulfonate with another monomer, a copolymer of styrene sulfonates and a monomer of maleic acid or anhydride monomer, polyacrylic acid, poly 2-acrylamido-2-methyl-propane sulfonate and an anionically-modifed polyvinyl alcohol.
- 12. (Currently amended) An element according to any one of claims 1 to 7, 10 and 11 as claimed in claim 1 wherein a polymer comprises a styrenesul fonate monomer.
- 13. (Currently amended) An element according to any one of elaims 1 to 7 as claimed in claim 1 wherein a polymer is a polyampholyte copolymer comprising a mixture of uncharged and pH-dependent negative and positive charges.
- 14. (Currently amended) An element according to as claimed
 in claim 13 wherein the polyampholyte is gelatin or a gelatin derivative.
- 15. (Currently amended) An element according to any one of the preceding claims as claimed in claim 1 wherein the total weight of polymer based upon volume of the colloidal particles is about 10 to about 40%.
- 16. (Currently amended) An element according to any one of the preceding claims as claimed in claim 1 wherein the ratio of a polymer or polymers of one charge type to that of another polymer or polymers of another charge type is not more than about 100:1.
- 17. (Currently amended) An element according to any one of the preceding claims as claimed in claim 1 wherein the image-receiving layer contains a binder selected from the class consisting of a poly(vinylalcohol), poly(vinyl acetate), styrene acrylic latex and styrene butadiene latex.

- 18. (Currently amended) An element according to any one of the preceding claims as claimed in claim 1 wherein the image-receiving layer contains one or more mordants.
- 19. (Currently amended) A method of coating a substrate comprising the steps of
- (a) providing colloidal particles having a charged or chargeable surface;
- (b) combining the colloidal particles with at least two <u>water-soluble</u> polymers having ionised or ionisable groups thereon, one of those polymers having ionised or ionisable groups of opposite charge to that of the surface of the colloidal <u>particles and another of those polymers having ionised or ionisable groups the</u> same as that of the surface of the colloidal particles to provide a coatable formulation;
- (c) applying the formulation to the substrate to form a coating thereon and
 - (d) drying the resultant coating.
- 20. (Currently amended) A method according to as claimed in claim 19 wherein the at least two polymers are added either sequentially and/or as a mixture.
 - 21. (Cancelled)
 - 22. (Cancelled)
- 23. (Currently amended) A method according to any one of elaims 19 to 22 as claimed in claim 19 wherein the substrate is paper, resin-coated paper or a transparent support.
- 24. (Currently amended) A method according to any one of elaims 19 to 23 as claimed in claim 19 wherein the formulation is coated onto the substrate by a pre-metered or post-metered coating method.

- 25. (Currently amended) A method according to any one of claims 19 to 24 as claimed in claim 19 wherein the coating formulation comprises at least 4% by volume of colloidal particles.
- defined in any one of claims 2 to 7 and at least two polymers as defined in any one of claims 8 to 14 to provide as inkjet element as defined in claim 1 to provide an inkjet element providing improved image stability and dry time having a charged or chargeable surface and at least two polymers having ionised or ionisable groups thereon to provide an inkjet recording element comprising a support having thereon at least one image-receiving layer, said inkjet recording element containing said colloidal particles and having associated therewith said at least two water-soluble polymers, wherein one of those polymers has ionised or ionisable groups of opposite charge to that of the surface of the colloidal particles and another of those polymers has ionised or ionisable groups the same as that of the surface of the colloidal particles.
 - 27. (Currently amended) An inkjet printing method comprising the steps of
- (a) providing an inkjet printer that is responsive to digital data signals;
- (b) loading the printer with an inkjet recording element as defined in any one of claims 1 to 18 comprising a support having thereon at least one image-receiving layer, said inkjet recording element containing colloidal particles having a charged or chargeable surface and having associated therewith at least two water-soluble polymers having ionised or ionisable groups thereon, wherein one of those polymers has ionised or ionisable groups of opposite charge to that of the surface of the colloidal particles and another of those polymers has ionised or ionisable groups the same as that of the surface of the colloidal particles;
 - (c) loading the printer with an inkjet composition; and
- (d) printing on the inkjet recording element using the inkjet composition in response to the digital data signals.